

UPKEEP & MAINTENANCE

Best Practice: Use of clean cotton gloves when handling product elements will ensure a good result and a ceiling without fingermarks. Handling the untreated panels with care will avoid damage and surface contamination prior to painting and thereby ensure a good end result

PRODUCT CATEGORY	NON-DEMOUNTABLE CEILINGS AND WALL LININGS
Products	Strata, Sonus, Stratum
Surface	Untreated / Paper Face
Upkeep	Designed for use under normal conditions, i.e. up to 70% RH and 25°C, e.g. in offices, institutions and similar premises.
Cleaning	Dust is removed using a dry duster or vacuum cleaner. Removal of marks depends on the paint used on site, although a damp cloth using normal cleaning practices and neutral cleaning solutions is normally suitable for minor marks. In the case of stubborn marks or if in doubt refer to the paint manufacturer's recommendations.
Repair	Use a paint roller to apply paint. Use the same paint as the original surface finish chosen. In case of surfaces painted with Medifend, make sure to use Medifend paint when repainting. Spray painting is not recommended on perforated products, as there is a great risk of the spray paint being applied to the acoustic felt backing thereby altering the acoustical properties.
Lighting/Mechanical	Items must be suspended from the deck/structure or furring system which must be able to bear the full weight.